

Automobile water temperature sensor

汽车水温传感器

产品特点 PRODUCT FEATURES

本产品采用高精度、高稳定性的单端玻璃封装NTC电阻封装，温度探头采用铝材，导热快，带有防尘塞，有效保证产品的清洁度。

This product adopts high-precision and high stability single ended glass encapsulated NTC resistors encapsulated, the temperature probe is made of aluminum material, with fast thermal conductivity and dustproof plug, which is effective ensure the cleanliness of the product.



工作参数 OPERATION PARAMETERS

- 电阻参数: $R_{25}=5K\Omega\pm 1\%$
 $B_{25/50}=3950K\pm 1\%$
 - 工作温度: -40 to $+130^{\circ}C$
 - 耐压测试: 1000V AC 0.5mA 1Sec
 - 绝缘电阻: 500VDC 100M Ω
 - 响应时间: $\leq 5s$
 - 工作电压: $5\pm 0.1VDC$
 - 工作电流: $\leq 0.5mA$
 - 对插件: 护套住友61896905端子住友81003067
- Resistance parameters: $R_{25}=5K\Omega\pm 1\%$
 $B_{25/50}=3950K\pm 1\%$
 - Operating temperature: -40 to $+130^{\circ}C$
 - Pressure resistance test: 1000V AC 0.5mA 1Sec
 - Insulation resistance: 500VDC 100M Ω
 - Temperature response time: $\leq 5s$
 - Supply voltage: $5\pm 0.1VDC$
 - Supply current: $\leq 0.5mA$
 - The plug-in models is:61896905